



CPCD140-160 WIDE VIEW MAST

Mast name	Max.fork Height (mm)	Overall height (mm)	Capacity kg			Tilt angle (F/B)	Total weight(KG)			Remarks
			CPCD140	CPCD160	CPCD160 (1200)		CPCD140	CPCD160	CPCD160 (1200)	
M300	3000	3300	14000	16000	16000	6°/12°	22500	23500	24700	standard equipment
M350	3500	3550	14000	16000	16000	6°/12°	22900	23900	25100	
M400	4000	3800	14000	16000	16000	6°/12°	23215	24215	25415	
M450	4500	4050	14000	16000	16000	6°/12°	23265	24265	25455	
M500	5000	4350	14000	16000	16000	6°/6°	23385	24385	25575	
M550	5500	4600	13000	15000	15000	3°/6°	23595	24595	25785	
M600	6000	4900	12000	14000	14000	3°/6°	24015	25015	26205	
M650	6500	5150	11000	13000	13000	3°/6°	24165	25165	26355	

CPCD200-CPCD250 WIDE VIEW MAST

Mast name	Max.fork Height (mm)	Overall height (mm)	Capacity kg		Tilt angle (F/B)	Total weight(KG)		Remarks
			CPCD200	CPCD250		CPCD200	CPCD250	
M300	3000	3490	20000	25000	5°/10°	33160	34160	
M350	3500	3740	20000	25000	5°/10°	33480	34480	
M400	4000	4000	20000	25000	5°/10°	33800	34800	standard equipment
M450	4500	4240	20000	25000	5°/10°	34120	35120	
M500	5000	4540	20000	25000	5°/10°	34460	35460	
M550	5500	4790	20000	25000	3°/6°	34780	35780	
M600	6000	5090	20000	25000	3°/6°	35120	36120	
M650	6500	5340	20000	25000	3°/6°	35440	36440	

CPCD280-320 WIDE VIEW MAST

Mast name	Max.fork Height (mm)	Overall height (mm)	Capacity kg			Tilt angle (F/B)	Total weight(KG)			Remarks
			CPCD280	CPCD300	CPCD320		CPCD280	CPCD300	CPCD320	
M400	4000	4120	28000	30000	32000	6°/10°	40000	41500	43000	standard equipment

CPCD420-460 WIDE VIEW MAST

Mast name	Max.fork Height (mm)	Overall height (mm)	Capacity kg		Tilt angle (F/B)	Total weight(KG)		Remarks
			CPCD420	CPCD460		CPCD420	CPCD460	
M400	4000	4850	42000	46000	6°/10°	55000	57200	standard equipment